Patent Pending

PSI 1500

SLP Guardian Seal

CITADEL ROUND

CITADEL Round[™] Combination of the Citadel Enclosure line's best features in a Smaller ROUND unit for tight areas that need LED light. Latches are replaced with the new SLP PinSert[™] System giving it a super sleek and clean look.



APPLICATIONS:

- Low Bay Areas that Require a Smaller LED Enclosure
- Replacement for Existing Round Installations
- Ideal for both Industrial and Architectural Environments

FEATURES & BENEFITS:

- Compact Size
 Nominal 18" Round, 6" Tall
- Designed for complete compatibility with LEDs
- New Pinsert[™] System (Patent Pending) with a poured in place gasket seals the enclosure from hostile environments
- No bulky latches
- Familiar Economical Mounting Options: SLP Hook, Pendant, J-Box Housing(CTR-HV5-18-PIP-JB), Gripple cable

LED MODULE BY LumaSmart:

- 13" Round DC Module, Single Channel
- Max LED operating temperature 85°C
- Material: MCPCB
- Thickness: 0.063", Dimension (D): 12.5", Cu: 2 oz.
- Single-Layer
- Color: White, Silkscreen: Black
- Lumen Maintenance: L85 >50Khrs using LM80 testing and TM-21 calculations
- Color Consistency: <3 SDCM (3000K –4000K)
- RoHS Compliant



Model Number	Lumens at 400K/80CRI	Nominal Input Current (mA)	Nominal Power (W)	Forward Voltage (VDC)	Lumens Per Watt	Diameter
LS3583A (13" Lowbay, Single channel)	16,209	2310 x 1	90	39.00	180	13"
LS3583B (13" Lowbay, Single channel, Performance)	18,500	2310 x1	94	41.10	196	13"

V10162020 Product offering and specifications subject to change without notice.



SLP LIGHTING 1400 S. Old Highway 141 Fenton, MO 63026 636-600-4084 www.slplighting.com



LumaSmart 15809 Claire Ct. Macomb Twp., MI 48042 Chris Lee M: (404) 989 - 9261 www.lumasmart.com

CERTIFICATIONS UL Wet Location

- UL evaluated for 25° & 40° C ambient temperatures
- NSF International
- IP65, IP66, IP67
- RoHS
- Separate Driver and LED Board Mounting Surfaces
- Flat Round LED Reflector Tray
- Board Retention Clips Snap Board Into Place Quickly
 Scratch Proof And Conductivity Inhibitor Coating On Clips
- Very tough diffusers resist breakage and reduce replacement costs
 - Water Clear or Full Frosted
- Utilizes off the shelf 1/2" and 3/4" NPT fittings