








	CTVS	CT2-NARROW	CT2-WIDE	CT4S	CT4	CT4I	CTR
<b>SLP Lighting Citadel Line</b>	Citadel Value Series	Citadel 2 1L4	Citadel 2	Citadel 4s	Citadel 4	Citadel 4I (CT4I-HV5-BR)	Citadel Round
							
<b>Purpose</b>	Low cost general LED lighting fixture	Narrow 1 Row body Citadel 2 family	Citadel 2 Wide 2Row body enclosure.	The short version of the Citadel 4/4i.	Wide 4 Row 4' High Bay Unit	A heavy duty industrial version of the Citadel 4	All the best Citadel features in a round unit.
<b>Size</b>	4' linear (51.75L x 4.10"W x 4.29"H)	4' Linear (51.75"L x 4"W x 4" H)	2', 4' and 8' Linear (27.7"L, or 51.8"L, or 100"L x 6.4"W x 5.7"H)	2' Linear (26.5"L x 14.5"W x 5.8" H)	4' Linear (51.9"L x 14.6"W x 5.9" H)	4' Linear (51.97"L x 14.6"W x 6.05" H)	18" Diameter (17.9" Diam x 5.34" H)
<b>Housing Material</b>	5VA Polycarbonate with Pour-in-Place gasket	5VA Fiberglass with Pour-in-Place gasket	5VA Fiberglass with Pour-in-Place gasket	5VA Fiberglass with Pour-in-Place gasket	5VA Fiberglass with Pour-in-Place gasket	5VA Fiberglass with Pour-in-Place gasket	5VA Fiberglass with Pour-in-Place gasket
<b>Max Wattage (1) @25C (@40C)</b>	75W (55W)	75W (54W)	2' - 75W (54W) 4' - 150W (100W) 8' - 300W (200W)	150W (100W)	300W (200W)	300W (200W)	150W (100W)
<b>IP Ratings</b>	IP65, IP66, IP67	IP65, IP66, IP67	IP65, IP66, IP67	IP65, IP66, IP67, IP69	IP65, IP66, IP67	IP65, IP66, IP67	IP65, IP66, IP67, IP69
<b>Certifications</b>	UL, NSF, RoHS	UL, NSF, NEMA 4X, RoHS	UL, NSF, NEMA 4X, RoHS	UL, NSF, NEMA 4X, RoHS	UL, NSF, NEMA 4X, RoHS	UL, NSF, NEMA 4X, RoHS	UL, NSF, RoHS
<b>Outdoor (f1) Rated</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Available Lenses</b>	Acrylic and Polycarbonate, in clear or FR50 frost, smooth or ribbed	Acrylic and Polycarbonate, in clear or FR50 frost, smooth or ribbed	Acrylic and Polycarbonate, in clear or FR50 frost, smooth or ribbed	Acrylic and Polycarbonate, in clear or FR50 Frost	Acrylic and Polycarbonate, in clear or FR50 Frost	Acrylic and Polycarbonate, in clear or FR50 Frost	Acrylic and Polycarbonate, in clear or FR50 Frost
<b>Lens Attachment Options</b>	POM Clips, White POM plastic and 316 SS latches	White POM plastic, Clear Polycarbonate, and 316 SS latches	White POM plastic, Clear Polycarbonate, and 316 SS latches	316 SS Clips, White POM plastic and 316 SS Latches	316 SS latches	White POM plastic and 316 SS latches	Patented SLP Pinsert System
<b>Mounting Options</b>	Ceiling, Pendant, Gripple cable or chain	Ceiling, Pendant (single or dual point), Gripple cable or chain	Ceiling, 45 degree, Pendant, Gripple cable or chain	Ceiling, Cable, Rigid Mount Beam, Pendant	Ceiling, Cable, Pendant	Ceiling, Gripple Cable or Chain, Rigid Mount Beam, Pendant	SLP Hook, Pendant with SLP Hub, J-Box Housing, Direct Mounting Bracket
<b>Typical Applications</b>	Stairwells, Storage Rooms, Under Awnings, Open Bays, Garden Centers	Parking Garages, Garden Centers, Stairwells, Storage, Under Awnings, Food Processing, Natatoriums, Gyms, Rec-Plexes	Parking Garages, Food Processing, Exterior Retail, Refrigerated Storage, Pedestrian Tunnels, Marinas and Offshore, Breweries and Bottling Facilities, Livestock Containment, Natatoriums, Gyms, Rec-Plexes	Parking Garages, Food Processing, Low Bay Areas, Storage, Under Awnings, Natatoriums, Gyms, Rec-Plexes	Refrigerated Storage, Parking Garages, Food Processing, Ext. Retail, Beverage and Bottling Facilities, Construction Sites, Gymnasiums, Livestock Containment, Manufacturing, Freezers, Natatoriums, Gyms, Rec-Plexes	Refrigerated Storage, Parking Garages, Food Processing, Exterior Retail, Beverage and Bottling Facilities, Construction Sites, Gymnasiums, Livestock Containment, Manufacturing, Freezers, Natatoriums, Gyms, Rec-Plexes	Low Bay Areas requiring smaller LED Enclosures, Replacement for Existing Round Installations, Ideal for both Industrial and Architectural Environments

(1) For comparative use only – max wattage noted can vary depending on the thermal management design-in properties used. Component thermal limits may be different for each LED engine, LED lamps or fluorescent lamps used, Contact SLP Engineering for Design-In Support.

 Manufactured in the USA

